

Analog Addressable Fire Panel



Features:

- 1/2 Loop CLIP Only
- Non-Networkable
- Up to 2 Loops
- Up to 99 detectors & 99 Modules per loop
- On Site & Off Site Programmable
- Non-proprietary programming tools
- Walk test facilities
- Designed and made in Australia
- 1/4 VGA Screen making operation simple
- 4000+ event history
- Optional QWERTY Keyboard
- Dedicated fan control modules
- Single button group isolate facility
- PLC style plain logic script programming
- Auto program functions
- Complete upload & download to Laptop
- Firefighters & Service Mode options
- Supports multi criteria detectors
- Supports addressable beam detectors
- Easy to program
- Comms ring supports distributed i/o
- Remote LCD mimics available
- Backwards compatible with existing Notifier panels
- Optional panel event printer
- Graphic control station PC capabilities

Description:

The FireSense **AFP-2802** is a cost effective, 1 or 2 CLIP loop, Non-Networkable version of the AFP-2800 fire panel, ideal for standalone installations.

It is an intelligent, non-proprietary, analogue addressable fire alarm control panel designed and manufactured in Australia by Notifier/Inertia and features a full off line and on line programming suite.

This FIP has the capacity for 2 CLIP loops, each with 99 detectors and 99 modules per loop and supports a full range of CLIP devices including thermal, smoke, duct, multi-sensor and beam detectors.

The modular hardware design and flexible programming allow the user to easily configure the AFP-2800 on site or remotely.

The AFP-2800 uses a 1/4 VGA screen and can display more than 17 lines of text on the screen at one time to prevent unnecessary scrolling in alarm conditions.

The AFP-2800 is approved to AS4428.1 and is one of the most technically advanced fire panels currently available on the Australian market.

Distributors For:



Unit 6
16 Lexington Drive
Bella Vista NSW 2153
Australia

PO Box 7026
Baulkham Hills BC
NSW 2153
Australia

tel 02 8850 2888
fax 02 8850 2999
www.firesense.com.au

Specifications:

Cabinet:	Zinc sealed steel	
	Powder coated (Charcoal)	
	Hinged inner door	
	Hinged outer door	
	003 Keyed lock	
Dimensions:	2800-650-1L-5A	650mm H x 450mm W x 192mm D
	2800-900-1L-5A	900mm H x 450mm W x 192mm D
	Battery Box	300mm H x 610mm W x 190mm D
AC Operational Voltage:	240 VAC 50 Hz±10%	
Power Supply:	1 Loop	2.6 Amp
	2 Loops	2.6 Amp
Battery Charger:	21.0 - 27.6 VDC	
Max Loops:	2	
Loop Capacity*:	CLIP 99 detectors & 99 modules	

Approvals:

SSL Approved	to AS 4428.1
ActivFire Listing No.	afp-1801

Distributors For:



Unit 6
16 Lexington Drive
Bella Vista NSW 2153
Australia

PO Box 7026
Baulkham Hills BC
NSW 2153
Australia

tel 02 8850 2888
fax 02 8850 2999
www.firesense.com.au