

**CLIP Analog Addressable
Thermal Detector**



Detector Sensitivity Table	
Sensitivity Level	Degrees Celsius
1	43
2	57
3	65 ("Type B")
4	70
5	75
6	88 ("Type D")

Description:

The SSF-B is a CLIP analog addressable fixed point thermal detector for use with 2800 Series fire alarm panels.

Detector sensitivity can be programmed in the control panel software. Sensitivity is continuously monitored and reported to the panel. Address setting on detectors is via two convenient dials on the base of the detector.

The SSC-B detectors include a reed switch which can be activated with a test magnet for ease of testing.

Specifications:

Detectors Per Loop (total):	99
Operating Voltage Range:	15 to 28 VDC
Standby Current:	300 μ A @ 24 VDC
Maximum Alarm Current (LED on):	6.5 mA @ 24 VDC
Operating Humidity Range:	10% to 93% Relative humidity, non-condensing
Operating Temperature Range:	-10 ° to 99°C

Approvals:

SSL Approved	
ActivFire Listing No.	afp-1767 (Notifier Model FDX-751BAUS)

Distributors For:



Unit 6
16 Lexington Drive
Bella Vista NSW 2153
Australia

PO Box 7026
Baulkham Hills BC
NSW 2153
Australia

tel 02 8850 2888
fax 02 8850 2999
www.firesense.com.au