

**FLASHSCAN Analog Addressable
Photo Optical Smoke Detector**



Detector Sensitivity Table		
Sensitivity Level	Alarm Obscuration % per Metre	Pre-Alarm Obs % per Metre
1	0.5 - 1.64	Auto
2	2.40	0.98
3	3.15	1.54
4	3.90	2.10
5	4.69	2.66
6	5.45	3.25
7	6.30	3.81
8	6.96	4.36
9	7.71	4.92

Description:

The SSF-P is a FLASHSCAN analog addressable photo optical detector for use with 2800 series fire alarm panels.

FlashScan supports 159 detectors per Loop. Detectors will also run on 2800's in CLIP mode or older Notifier panels together with CLIP devices with maximum address restricted to 99.

Detector sensitivity can be programmed in the control panel software. Sensitivity is continuously monitored and reported to the panel. Address setting on detectors is via two convenient dials on the base of the detector.

Detectors use an easily removable cover (for cleaning purposes).

Detectors include a reed switch which can be activated with a test magnet for ease of testing.

Specifications:

Detectors Per Loop (total):	159
Plastic Colour	System Sensor Commercial White
Operating Voltage Range:	15 to 32 VDC
Standby Current:	300 µA @ 24 VDC
Maximum Alarm Current (LED on):	6.5 mA @ 24VDC
Operating Humidity Range:	10% to 93% Relative humidity, non-condensing
Operating Temperature Range:	-10 ° to 49°C

Approvals:

SSL Approved	
ActivFire Listing No.	afp-1634 (Notifier Model FSP-851AUS)

Distributors For:



Unit 6
16 Lexington Drive
Bella Vista NSW 2153
Australia

PO Box 7026
Baulkham Hills BC
NSW 2153
Australia

tel 02 8850 2888
fax 02 8850 2999
www.firesense.com.au